

## Digital Hand-held "Pocket" Lactose Refractometer PAL-19S











Quantity Request Quotation

about the icons .		žó.o	PATC	$\stackrel{\text{\sc ss}}{lack}$	∰ EU

## **Specifications**

Model	PAL-19S
Cat.No.	4419
Scale	Lactose (g/100g) Temperature
Measurement Range	Lactose : $0.0 \text{ to } 20.0\% \text{ (g/100g)}$ Temperature : $10.0 \text{ to } 40.0^{\circ} \text{ C}$
Resolution	Lactose: 0.1% Temperature: 0.1° C
Measurement Accuracy	Lactose: $\pm 0.2\%$ Temperature: $\pm 1^{\circ}$ C
Temperature compensation range	10 to 40° C (Automatic Temperature Compensation)
Ambient Temperature	10 to 40° C
Sample Volume	0.3 mL
Measurement Time	3 seconds
Power Supply	2 x AAA Batteries
Battery Life	Approx. 11,000 times measurement (when alkaline batteries are used)
International Protection Class	IP65 Dust-tight and Protected against water jets.
Dimensions & Weight	55(W) x 31(D) x 109(H)mm, 100g (Main Unit only)

## Options

· PAL-CASE: RE-39409

· PAL Silicone Cover: RE-39413

· STRAP: RE-39410

Patent for Invention Registration No. ZL200310103015.2 (China)
Patent for Design Registration No. ZL03303431.1 (China), 089244 (Taiwan)
Patent Granted in countries around the world.

